SAFETY INFORMATION

If the vehicle to be worked on is raised, ensure that it is adequately supported with axle stands or ramps and chocks. If working off the vehicle, make sure that the workplace is secure and stable.



- > Use these tools only in accordance with industry best practices and all applicable local and national regulations. Do not use them for unintended tasks.
- > DO NOT use with missing or damaged parts.
- > Wear suitable clothing during use. DO NOT wear loose jewelry or clothes and tie back any long hair.
- > D0 NOT use when tired or under the influence of drugs, alcohol, or intoxicating medication.
- > DO NOT use with air/pneumatic tools.
- > Ensure the strut is secure and stable before beginning compression.
- > Ensure the jaws are correctly engaged before beginning compression.

- > DO NOT under any circumstances attempt to dismantle the strut until the spring compressors are in place and the spring has been sufficiently compressed.
- Ensure the jaws and body of the compressor remain correctly aligned at all times during spring compression.
- > STOP compressing the spring before it comes coil bound or the coil windings or jaws touch.
- > DO NOT leave a compressed spring unattended.
- > D0 NOT allow children or untrained persons to use this spring compressor set.
- Maintain these tools in good condition. For best results, clean after each use. Replace or repair any damaged parts before next use.

MAINTENANCE

BEFORE EACH USE

Inspect the general condition of these tools. Check for misalignment or binding of moving parts, cracked or broken parts, and any other condition that may affect safe operation. If any defect is apparent or any abnormal noise or vibration occurs during use, have the problem corrected before further use of these tools.

AFTER EACH USE


Wipe clean with a damp cloth, using a mild detergent or mild solvent. Keep the compressor spindles lubricated and keep the compressor clean. When not in use store this tool kit in its case in a safe, dry, childproof location.

PARTS LIST		
Item #	Description	Specification
1	Strut Spring Compressor Tool	Drive: 19mm Hex Max. Reach: 11.4 in (29 cm) Capacity: 1200 lb. (544kg)
2	Coil Compressor Brackets	Extends from 8-11.7 in. (203-297 mm)



OPERATION

- 1. Remove the strut from your vehicle according to the procedures recommended in its manufacturer's manual.
- 2. Put the jaws (C) into position and engage them in the spring as far apart as possible as shown in Fig. 1. Ensure that the jaws are correctly aligned, making sure the two arms are parallel to each other as in Fig. 2.
- 3. Put the tools into position as shown in Fig. 1. Tighten the lower jaws around the lowest part of the spring using their locking ring (B).
- 4. Tighten the compressor by turning the two 19mm hex adjuster bolts (D) clockwise using a suitable wrench. The coil will need to be compressed equally on each side. Alternate between each arm so as to not unbalance the spring. Compress the spring without allowing it to become bound
- 5. When the spring is fully compressed and is free to rotate on the strut, remove the top place from strut and withdraw the spring.
- 6. Reverse this procedure to replace the spring.





MISHIMOTO LIFETIME WARRANTY

Mishimoto Automotive ("Mishimoto") warrants its products under this lifetime limited warranty policy ("Warranty Policy"). This Warranty Policy applies solely to: (i) Mishimoto Products purchased directly from Mishimoto or Mishimoto authorized dealers (each a "Mishimoto Product" and collectively, the "Mishimoto Products") and (ii) the original purchaser of such Mishimoto Product ("Purchaser"). This Warranty Policy is non-transferable and all claims under this Warranty Policy must be accompanied by the original sales receipt. The terms and conditions of this Warranty Policy are subject to change by Mishimoto at any time without notice.

Pursuant to the terms and conditions of this Warranty Policy, after submission of a valid claim by a Purchaser and regardless of the condition of the product for which such valid claim is submitted, if it is determined by Mishimoto that such Mishimoto Product was not manufactured to Mishimoto's advertised specifications or if such claim was submitted pursuant to Mishimoto's Accident Protection Plan, as described herein, Mishimoto will, at its discretion: (i) repair or replace Purchaser's original Mishimoto Product with the most current available model (if, for example, the original model of the product for which a valid claim has been submitted is not available); or (iii) provide the purchaser with a gift card redeemable at Mishimoto.com in the amount of the original purchase price of the original Mishimoto Product (if, for example, Mishimoto has discontinued support for a Purchaser's specific application).

To submit a claim for a Mishimoto Product under this Warranty Policy, you must: (i) fully and accurately fill out the Online form provided below; and (ii) provide Mishimoto with a copy of an original sales receipt indicating that you are the original Purchaser of the Mishimoto Product for which the claim is being submitted (you must also provide the information described in the paragraph of this Warranty Policy titled "Mishimoto Accident Protection Plan" if you are submitting a claim for a Mishimoto Product damaged in an accident). In addition, if requested by Mishimoto, you must also send the Mishimoto Product for which a claim is being made, all transportation expenses prepaid, to Mishimoto.

General Disclaimer of Warranties

THE WARRANTIES SET FORTH HEREIN ARE THE ONLY WARRANTIES MADE BY MISHIMOTO IN CONNECTION WITH THE MISHIMOTO PRODUCTS. MISHIMOTO CAN NOT AND DOES NOT MAKE ANY IMPLIED OR EXPRESS WARRANTIES WITH RESPECT TO THE MISHIMOTO PRODUCTS, AND DISCLAIMS ALL OTHER WARRANTIES, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. PRODUCTS SOLD BY MISHIMOTO ARE SOLD ONLY TO THE SPECIFICATIONS SPECIFICALLY SET FORTH BY MISHIMOTO IN WRITING. OTHER THAN THE LIMITED WARRANTY SET FORTH HEREIN, MISHIMOTO MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. MISHIMOTO'S SOLE OBLIGATION UNDER THIS WARRANTY SHALL BE REPAIR OR REPLACEMENT OF NON-CONFORMING PRODUCTS AS DESCRIBED HEREIN, OR AT THE OPTION OF MISHIMOTO, RETURN OF THE PRODUCT AND THE PROVISION OF A GIFT CARD REDEEMABLE AT MISHIMOTO.COM IN THE AMOUNT OF THE ORIGINAL PURCHASE PRICE OF SUCH PRODUCT. PURCHASER ASSUMES ALL RISK WHATSOEVER AS TO THE RESULT OF THE USE OF THE MISHIMOTO PRODUCTS PURCHASED, WHETHER USED SINGULARLY OR IN COMBINATION WITH ANY OTHER PRODUCTS OR SUBSTANCES.

Limitation of Liability

No claim by the Purchaser of any kind, including claims for indemnification, shall be greater in amount than the purchase price of the Mishimoto Product in respect to which damages are claimed. IN NO EVENT SHALL COMPANY BE LIABLE TO THE PURCHASER IN TORT, CONTRACT OR OTHERWISE, FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, RELIANCE, STATUTORY, SPECIAL, PUNITIVE OR EXEMPLARY DAMAGES, INCLUDING, BUT NOT LIMITED TO, LOST PROFITS, LOSS OF USE, LOSS OF TIME, LOSS OF REVENUES, INCONVENIENCE, LOSS BUSINESS OPPORTUNITIES, DAMAGE TO GOOD WILL OR REPUTATION, OR LOSS OF DATA, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR SUCH DAMAGES COULD HAVE BEEN REASONABLY FORESEEN, IN CONNECTION WITH, ARISING OUT OF, OR AS A RESULT OF, THE SALE, DELIVERY, SERVICING, USE OR LOSS OF LOSS OF THE MISHIMOTO PRODUCTS SOLD HEREUNDER. OR FOR ANY LIABILITY OF PURCHASER TO ANY THIRD PARTY WITH RESPECT THERETO.

To read our full warranty policy, please visit www.mishimoto.com/lifetime-warranty.



SPRING COMPRESSOR TOOL KIT USER MANUAL

